



ARTICLES IN ABRASIVE CLOTH

The abrasive cloth items are made up with coated abrasives, in the various grits, of qualified European producers, to satisfy the requirements of grinding, deburring, satin finishing on ferrous and non ferrous metals.

The articles in abrasive cloth work without abrasive compounds. However, it is recommended to lubricate by TALLOW compounds.

art. 1707 rolls of abrasive cloth
length 50-100 mt. (or at request)
width at request

art. 1708 jointed belts of abrasive cloth
length and width at request

art. 1702 flap wheels of abrasive cloth

STANDARD DIMENSIONS IN MM. OF FLAP WHEELS
ART. 1702

external ϕ	internal bore	thickness
165	54	30-50
200	54	30-50
250	100	30-100
300	100	30-100
350	170	30-100
400	170	30-100

art. 1703 flap wheels of abrasive cloth with drive pin

STANDARD DIMENSIONS IN MM. OF FLAP WHEELS
ART. 1703

external ϕ	internal bore	thickness
30	6	50-20
40	6	10-30
50	6	10-30
60	6	15-50
80	6	15-50



PRESSURE

Use only a slight pressure, as the work is done by the abrasive and not by the force exerted by the operator or the machine. Excessive pressure results in rapid wear and unsatisfactory finish.